

n._Sci._1117_012012-
EffectOfEucalyptus...SoftSoil-
ASLI.pdf
by

Submission date: 08-Jan-2023 03:13PM (UTC+0700)

Submission ID: 1989681782

File name: n._Sci._1117_012012-EffectOfEucalyptus...SoftSoil-ASLI.pdf (480.09K)

Word count: 2254

Character count: 13989

PAPER · OPEN ACCESS

Effect of eucalyptus pellita timber-pvd hybrid pile as a vertical drain on soft soil.

10
To cite this article: Suyadi *et al* 2022 *IOP Conf. Ser.: Earth Environ. Sci.* 1117 012012

2
View the [article online](#) for updates and enhancements.

You may also like

- 5
[Research on Change Laws of Pore Water Pressure of Soft Clay in the Large-scale Wave Flume](#)
Liu Zhen, Cheng Yongzhou, Zhang Huaqing et al.
- 3
[The Effect of variations in PVD installation distance and thickness of soft soil layer for the degree of consolidation and time of consolidation at Gunung Anyar, Surabaya](#)
M K Wardani and Naufan
- [The Potential of Soft Soil Improvement Through a Coupled Technique Between Electro Kinetic and Alkaline Activation of Soft Soil](#)
G E Ahmed, H B Ismail, B K Huat et al.


ECS Toyota Young Investigator Fellowship

For young professionals and scholars pursuing research in batteries, fuel cells and hydrogen, and future sustainable technologies.

At least one \$50,000 fellowship is available annually.
More than \$1.4 million awarded since 2015!



Application deadline: January 31, 2023



Learn more. Apply today!

Effect of eucalyptus pellita timber-pvd hybrid pile as a vertical drain on soft soil.

Suyadi¹ Tri Harianto² A B Muhiddin² A Arsyad²

¹Doctoral Student of Civil Engineering, Hasanuddin University, Gowa, South Sulawesi, Indonesia, 92171

²Departement of Civil Engineering, Hasanuddin University, Gowa, South Sulawesi, Indonesia, 92171

E-mail: suyadi19d@student.unhas.ac.id

Abstract The innovative technique of a hybrid PVD timber pile as a vertical drain can be implemented to reinforce and improve soft soil. In this case, the acceleration of pore water dissipation could increase shear strength. The at soil of this study is to investigate the effectiveness of a hybrid eucalyptus pellita-PVD timber pile as a vertical drain. The test method applied is a laboratory model test, consisting of the installation of a hybrid pile on soft soil in a rectangular pattern with a spacing of 10 cm. Then by a static loading test was subjected on soft soil with an initial load of 10 kg and subsequent loads of 20 kg and 40 kg. Daily dial monitoring of the increase in pore water dissipation was performed during the preloading test. The results show that the hybrid pile could accelerate the process of pore water dissipation to the surface compared to using timber piles alone. The increase of soil density before and after the loading indicated that the hybrid piles enhanced the density by 3.9%, whereas the reinforcement using only timber pile just increased by 2.4%.

Keywords: hybrid pile, eucalyptus pellita, vertical drain.

1. Introduction

As well as the expansion of the construction sector, the need for developing land will continue to rise. However, some regions are unable to avoid conditions in which building sector development must be conducted on soft soil. Soft soil has a poor bearing capacity, a high soil plasticity index, low permeability, and a prolonged subsidence process. These qualities pose the most significant challenges for designers who wish to construct a building atop it.

Construction on soft soil requires many solutions to the problems of limited bearing capacity and extended consolidation period. And this issue can be resolved by improving the carrying capacity of the soil through micropile installation. [1] [2] [3] [4] [5] [6] [7] and constructing one-way vertical drain might accelerate changes in soft soil water content and the process of land subsidence. [8] [9] As for the conductivity issue, PVD can be utilized to speed up the process of pore water dissipation caused by loading processes. [10] [11] [12].

In Indonesia, micro-piles are constructed with timber piles since indigenous materials are permitted in several regions, and the availability of these materials is relatively high, making this a viable option in areas where the soil conditions have a limited bearing capacity.

As a breakthrough in soil improvement and reinforcement engineering, hybrid Eucalyptus pellita-PVD timber piles are anticipated to raise the soil's bearing capacity and hasten the consolidation process. This study intends to assess the effect of constructing a rectangle pattern of Hybrid piles of eucalyptus pellita-PVD timber piles as vertical drain on the soft soil's water release.

2. Materials and Testing Methods

2.1. Materials

Based on the result of laboratory tests, which included testing the physical and mechanical properties of soft soil samples, test data on the characteristics of the eucalyptus pellita timber material, and test data on the characteristics of the Prefabricated Vertical Drain (PVD) material, the initial research data were gathered. This information is necessary to establish whether the type of material used corresponds to the required design and



description for the intended model test. This study utilized a soft soil sample from the Turikale, Maros Regency sub-district. The eucalyptus pellita timber originates from the Muting District of the Merauke Regency in South Papua Province. As indicated in Figure 1, the little timber pile has a length of 33 centimeters and a width of 1 centimeter. As shown in Figure 2, the Prefabricated Vertical Drain (PVD) length is 33 cm, and the width is 1 cm. Based on the shape of the two materials, two reinforcement models are created, the first of which consists of three connected timber piles. The second type uses wire, composed of three piles and one PVD in the center, as depicted in Figure 3.



Figure 1. Mikro pile eucalyptus pellita



Figure 2. Prefabricated Vertical Drain (PVD),



Figure 3. Timber Pile and Timber pile+PVD (hybrid pile)

2.2. Testing Methods

The applied research design refers to the collected primary and secondary data. This study includes two test models: a one-way vertical drain test using a timber cone + PVD (Hybrid pile) and reinforcement using timber piles without PVD, installing a 10-cm-wide rectangular pattern. This layer will serve as a control point for the process of releasing water to the surface by evaluating the water content daily during the testing procedure, as depicted in Figures 4, 5, and 6. Subsequently, the preloading test was conducted with a progressive load, starting with 10 kg, followed by 20 kg, and finally 40 kilograms. By measuring the moisture content of the sand every day for 27 days, the process of water rising to the surface was observed and quantified. Figures 7 and 8 show that the test implementation model is shaped and sized according to the test dimensions.




Figure 4. Installation position timber pile




Figure 5. Installation position Hybrid pile



Figure 6. Water content sampling



Figure 7. Test equipment installation position




Figure 8. Model and size test dimensions

3. Result and Discussion

4

Based on the results of testing the soil characteristics, the type of soil utilized for model testing according to the USCS classification was high plasticity clay (CH), whereas the classification according to AASHTO was group A-7-6. The summary of the soil characteristics test may be found in Table 1.

Table 1. Soil characteristics test results.

No.	Kinds of Test	Unit	Test Result
Characteristic of Physical Properties			
1	Specific Gravity (Gs)	-	2,74
2	Water Content (w)	(%)	72.91
3	Atterberg Limit		
	shrinkage limit (S.L.)	(%)	13.88
	Plastic Limit (P.L.)	(%)	26.77
	Liquid Limit (L.L.)	(%)	82.75
	Plasticity Index (PI)	(%)	55.98
4	Grain size analysis		
	Gravel	(%)	0.00
	Sand	(%)	7.20
	Silt	(%)	25.50
	Clay	(%)	67.30
5	Permeability	(cm/s)	2.3×10^{-7}
Classification			
	USCS		CH
	AASHTO		A-7-6

Based on the outcomes of laboratory tests on Eucalyptus Pellita timber used as timber piles, this species is classified as a timber class I [13]. Based on the results of investigating the qualities of the timber material used

for piles, the data presented in Table 2 were acquired. The characteristics of the Prefabricated Vertical Drain (PVD) material used in this investigation are of the CeTeau Drain CTD-812 type. This PVD has a permeability value of $> 1 \times 10^{-4}$ m/s, which is fairly high.

Table 2. *Eucalyptus Pellita* test results

No.	Kinds of Test	Unit	Test Result
1	Specific Gravity (Gs)	-	0.91
2	Water Content (w)	(%)	8.83
3	Flexural strength	Mpa	110.50
4	Compressive strength parallel to fiber	Mpa	60.15

Observations and testing of water content during the research period revealed that the use of a timber cone + PVD as a vertical drain on soft clay soils could accelerate the process of releasing surface water. At the initial time of loading, the increase in water content surface- cover sand and the graph repeats this pattern at the initial time of adding the second and third loads. Figure 9 depicts the graph of the relationship between the load and water content surface- cover sand.




Figure 9. Graph of load relationship and surface water content.

Table 3. The results of the water content and bulk density of the soil testing

Test Model	11 Before loading			11 After Loading		
	γ_{wet} (gr/cm ³)	γ_{dry} (gr/cm ³)	W (%)	γ_{wet} (gr/cm ³)	γ_{dry} (gr/cm ³)	w (%)
Timber pile	1.49	0.82	82.69	1.51	0.84	81.07
Timber pile + PVD (hybrid pile)	1.49	0.82	82.20	1.53	0.85	79.93

Table 3 presents the results of a comparison between the soft soil test values with timber pile reinforcement and the soft soil test values with hybrid pile (PVD) reinforcement as vertical drain. The results of this preloading test indicate that the density of the soft soil has increased. The indicator for this rise in density is the change in the original value of dry density before loading and reinforcing system installation. The initial dry density value

before loading was 0.82 kg/cm³ with a moisture content of 82%. However, following the application of timber pile reinforcement, the value increased to 0.84 kg/cm³ with a moisture content of 81.07%. Using a hybrid pile as vertical drain increased the soil's dry density to 0.85 kg/cm³ while decreasing the soil's water content to 79.93%.

This demonstrates that using timber piles and PVD (hybrid pile) can speed the soil compaction process. This situation emerges due to the PVD's function as a vertical drain system. Figure 10 depicts a comparison of the results of soil density tests. Figure 11 shows the variations in the moisture content of soft soil before and after loading. The results indicate that using Hybrid piles of Eucalyptus Pellita – PVD as vertical drain can enhance soil density by 3.9%, whereas the reinforcement that simply employs timber piles increases soil density by 2.4%.




Figure 10. Dry density value before and after loading test




Figure 11. Comparing the results of water content tests

4. Conclusion

The conclusions that can be drawn from this research are:

1. Installation of vertical drain Hybrid piles of Eucalyptus Pellita – PVD timber piles are able to accelerate the process of removing water from the soil when compared to reinforcement that only uses timber cones.
2. The use of Hybrid pile piles of Eucalyptus Pellita – PVD as vertical drain was able to increase soil density by 3.9%, while the reinforcement that only used timber cones was 2.4%.

5. Suggestion

It is necessary to conduct further testing with different installation patterns and depth variations to obtain an effective design and depth used for the installation of hybrid piles as vertical drain.

6. References

- [1] Harianto T., Djamaluddin R., Muhiddin A.B., Maricar I.& SitepuF 2012 *Characteristic sand Behaviour Study on Raft and Pile Bamboo as a Soil Embankment Reinforcement (in Indonesia)*.(Indonesia:Trisakti University), pp. G59-G65
- [2] Gasruddin Ahmad., Harianto T., Arsyad Ardy 2016 *Reinforcement of the Slope of Road Surface with Micro Root Pile Type in Soft Soil Deposite*.(Indonesia:Hasanuddin University), Vol.5 pp. 80–85.
- [3] Sandyutama, Y., Samang, L., Imran, A.M., Harianto, T., 2015 *Full Scale Model Test of Consolidation Acceleration on Soft Soil deposition with Combination of Timber Pile and PVD (Hybrid Pile)*. (IJIRAE), Volume 2, pp. 23-28
- [4] Moayed R.Z., Abolhassan Naeini S 2012 *Improvement of Loose Sandy Soil Deposits using Micropiles*. KSCE Journal of Civil Engineering, pp. 334-340
- [5] Mitrani .H and Madabhushi, S. P.G 2008 *Centrifuge modelling of inclined micro-piles for liquefaction remediation of existing buildings*. Geomechanics and Geoengineering An International Journal, pp. 245-256
- [6] Harianto, T., Yunus, M and Walenna, M.A 2011 *Bearing Capacity Of Raft-Pile Foundation Using Timber Pile On Soft Soil*, *International Journal of GEOMATE*, Vol.21(86)pp108-114. doi:10.21660/2021.86.j2294
- [7] Harianto T., Samang L., Suheriyatna and Sandyutama Y., 2016 *Field Investigation of the Performance of Soft Soil Reinforcement with Inclined Pile*, *Proc. of the 5th Geotech. & Geophysic. Site Characteristics*, Lehane, Acosta-Martinez & Kelly (Eds), pp. 1349-1352.
- [8] Abadi, T. C., 2004, *Uji Laboratorium Pemanfaatan Serabut Kelapa dan Ijuk Sebagai Bahan Drainase Vertikal Tanpa Filter*, (Indonesia:Institut Teknologi Nasional Bandung)
- [9] Prastyo, B., Setiawan, B., Indrabaskara, R. H. D. H., 2017 *Pengaruh Kedalaman Drainase Vertikal Satu Arah Menggunakan Kolom Pasir terhadap Kecepatan Penurunan dan Perubahan Kadar Air Tanah Lunak*, (Indonesia:Universitas Sebelas Maret)
- [10] Herwanto W 2012 *Studi Perbandingan Analisis Perbaikan Tanah Lunak Dengan Metode Prefabricated Vertical Drain Pada Berbagai Constitutive Model (Studi Kasus PT. Wilmar Nabati)*.(Indonesia: Institut Teknologi Bandung)
- [11] Juniarto 2011 *Analisa Waktu Penurunan Tanah Dengan Kombinasi Metode Preloading dan Prefabricated Vertical Drain (PVD) Antara Pola Segitiga dan Persegi Pada Perbaikan Tanah (Studi Kasus Landasan Pacu Bandar Udara Juwata Tarakan)*.(Indonesia; Lembaga Penelitian Universitas Gunadarma) ,pp. 91-99.
- [12] Harianto, T. 2022 *Performance of Subbase Layer with Geogrid Reinforcement and Zeolite-Waterglass Stabilization*, *Civil Engineering Journal*, Vol. 8(20), pp251-262. doi: 10.28991/CEJ-2022-08-02-05.
- [13] Yayasan Dana Normalisasi Indonesia, 1979. *Peraturan Konstruksi Kayu Indonesia NI-5 1961*. (Bandung: Yayasan Lembaga Penyelidikan Masalah Bangunan).

Acknowledgements

¹³ The authors would like to express their deepest gratitude for the financial support from the Education Fund Management Institute (LPDP), Ministry of Finance of the Republic of Indonesia. ⁸

ORIGINALITY REPORT

15%

SIMILARITY INDEX

12%

INTERNET SOURCES

12%

PUBLICATIONS

6%

STUDENT PAPERS

PRIMARY SOURCES

1	opus.lib.uts.edu.au Internet Source	3%
2	I Sperberga, M Rundans, A Cimmers, L Krage, I Sidraba. "Mechanical properties of materials obtained via alkaline activation of illite-based clays of Latvia", Journal of Physics: Conference Series, 2015 Publication	2%
3	www.proceedings.com Internet Source	2%
4	A Zhafirah, S Permana, M Daris, D Yogawsara. "Comparative analysis of soft soil consolidation time due to improvement using Prefabricated Vertical Drain", IOP Conference Series: Materials Science and Engineering, 2021 Publication	1%
5	Y N Zakharov, A I Zimin, I S Nudner, M E Yashin. "Mathematical modeling of a hydraulic flume for carrying out numerical experiments on coastal waves and erosion of	1%

cohesive soil", Journal of Physics: Conference Series, 2020

Publication

6	Submitted to California Unitec Student Paper	1 %
7	Submitted to School of Business and Management ITB Student Paper	1 %
8	www.researchgate.net Internet Source	1 %
9	"Geotechnics for Sustainable Infrastructure Development", Springer Science and Business Media LLC, 2020 Publication	1 %
10	Submitted to Universitas Gunadarma Student Paper	1 %
11	ejournal.unsri.ac.id Internet Source	1 %
12	jurnal.itats.ac.id Internet Source	1 %
13	repository.unair.ac.id Internet Source	<1 %
14	jurnal.uns.ac.id Internet Source	<1 %
15	www3.eng.cam.ac.uk Internet Source	

<1 %

Exclude quotes On

Exclude matches < 5 words

Exclude bibliography On