

10.JIKI_DorsalVeinLLBP.pdf

by

| | | | |
|----------------|--------------------------------------|-----------------|-------|
| FILE | 10.JIKI_DORSALVEINLLBP.PDF (731.14K) | WORD COUNT | 4743 |
| TIME SUBMITTED | 29-SEP-2019 02:01PM (UTC+0700) | CHARACTER COUNT | 24562 |
| SUBMISSION ID | 1182096453 | | |

See discussions, stats, and author profiles for this publication at: <https://www.researchgate.net/publication/326132088>

MULTISPECTRAL DORSAL HAND VEIN RECOGNITION BASED ON LOCAL LINE BINARY PATTERN

Article · June 2018

DOI: 10.21609/jiki.v11i2.576

CITATIONS

0

READS

36

4 authors, including:



Jayanti Yusmah Sari
Universitas Haluoleo

21 PUBLICATIONS 11 CITATIONS

SEE PROFILE

Some of the authors of this publication are also working on these related projects:

 Pattern Recognition View project

 VEIN RECOGNITION View project

MULTISPECTRAL DORSAL HAND VEIN RECOGNITION BASED ON LOCAL LINE BINARY PATTERN

Fransisca J. Pontoh, Jayanti Yusmah Sari, Amil A. Ilham, and Ingrid Nurtanio

Department of Electrical Engineering, Hasanuddin University, Makassar, 90245, Indonesia
Department of Informatics Engineering, Halu Oleo University, Kendari, 93231, Indonesia

E-mail: fransiscapontoh@gmail.com, ingrid@unhas.ac.id

Abstract

Nowadays, dorsal hand vein recognition is one of the most recent multispectral biometrics technologies used for the person identification/authentication. Looking into another biometrics system, dorsal hand vein biometrics system has been popular because of the privilege: false duplicity, hygienic, static, and convenient. The most challenging phase in a biometric system is feature extraction phase. In this research, feature extraction method called Local Line Binary Pattern (LLBP) has been explored and implemented. The straight-line shape of LLBP can extract robust features from the images with unclear veins therefore, recognition performance of dorsal hand vein image will be good. We have used this method to our 300 dorsal hand vein images obtained from 50 persons using a low-cost infrared webcam. In recognition step, fuzzy k -NN classifier is adopted since it does not need any learning algorithm, so that it can decrease the processing time. The experimental result showed that LLBP method is reliable for feature extraction on dorsal hand vein recognition with a recognition accuracy up to 98%.

Keywords: *biometrics, dorsal hand vein, fuzzy k-NN, local line binary pattern, vein recognition.*

Abstrak

Saat ini pengenalan *dorsal hand vein* merupakan salah satu teknologi terbaru dalam biometrika *multispectral* yang digunakan untuk mengidentifikasi seseorang. Dibandingkan dengan sistem biometrika lainnya, sistem biometrika berbasis *dorsal hand vein* lebih sering digunakan karena memiliki beberapa kelebihan seperti sulit untuk diduplikasi, higienis, bersifat tetap (tidak berubah-ubah) dan mudah (untuk diaplikasikan). Tahapan yang penting dalam sistem biometrika adalah tahap ekstraksi fitur. Dalam penelitian ini, dilakukan pengkajian dan pengimplementasian salah satu metode ekstraksi fitur yaitu Local Line Binary Pattern (LLBP). Bentuk filter LLBP yang berupa garis dapat menghasilkan fitur vein yang lebih jelas sehingga menghasilkan pengenalan *dorsal hand vein* yang lebih baik. Metode ini diuji menggunakan 300 citra pembuluh darah pada telapak tangan (*dorsal hand vein*) yang berasal dari 50 individu yang diakuisisi dengan *webcam* inframerah. Pada tahap pengenalan, metode fuzzy k -NN digunakan karena metode ini tidak membutuhkan algoritma pembelajaran sehingga diharapkan dapat mengurangi waktu pemrosesan. Hasil pengujian menunjukkan bahwa metode LLBP dan fuzzy k -NN memiliki kinerja yang baik untuk ekstraksi fitur pada pengenalan *dorsal hand vein* dengan akurasi pengenalan mencapai 98%.

Kata Kunci: *biometrika, dorsal hand vein, fuzzy k-NN, local line binary pattern, pengenalan pembuluh darah*

1. Introduction

Multispectral dorsal hand vein recognition is one of the most recent multispectral biometrics technologies used for the person identification because of its strengths. 1) The form of the vascular patterns in the dorsal hand is distinct from each other. 2) The image of a dorsal hand vein pattern can be captured only by a live body too. Thus, it is very difficult to falsify it [1]. 3) As the veins are internal features the state of the skin, humidity, temperature do not have much effect on the vein image [2]. 4) Since it acquires a dorsal hand vein

pattern image without direct contact with the hand or with the vein pattern-extracting sensor, there is no contamination [3] and 5) the pattern of the vessels of back of the hand is fixed and unique with repeatable biometric features [4].

Most of the currently available approaches for dorsal hand vein recognition have similarities on the feature extraction method. The examples of feature extraction methods which already used for hand vein recognition are Hough Transform [5], multi-scale second-order differential model [6], and Fuzzy-Neuro [7]. Those methods show a good performance due to the high qualities of hand vein




Figure 1. The overview of proposed method for dorsal hand vein recognition

images. However, sometimes hand vein images are not clear due to the qualities of sensor or noise. Unclear extracted vein can become the problem in hand vein recognition.

[14], [8] conducted palm vein recognition using Local Binary Pattern (LBP) features. Local Binary Pattern (LBP) is a feature that resist variations of illumination conditions [9]. LBP stores the texture pattern into the binary vector where each binary value is obtained by the result of the difference between the central pixel with the neighbourhood pixels. Although the result of this difference is not influenced by varying illumination conditions [10], but shape-based feature extraction puts the forward higher requirement for the original image. Specifically, the vein edge should be clear to avoid the occurrences of the broken and blurred vein. It may affect recognition process and degrades recognition accuracy. So that, it is important to focus on capturing vein pattern in a segmented blood vessel network and utilized the features from the segmented blood vessel network for recognition.

In the recent years, some research conducted the experiment using a new variant of LBP called local line binary pattern (LLBP) [11] to overcome the problem of unclear extracted finger vein [2] and palm vein [12]. Those experiments result in the EER of 1.89% and accuracy of 97.3% respectively. Therefore, it is evident that the LLBP method can achieve good performance in the accuracy of finger-vein and palm-vein recognition system although it is proposed for the first time by [13] in 2009 face recognition system.

Local Line Binary Pattern (LLBP) is a good oriented feature representation method extended from local binary pattern (LBP) [14]. The main difference between LLBP and LBP is its neigh-




Figure 2. The dorsal hand vein image acquisition



Figure 3. The sample of captured dorsal hand vein image




Figure 4. The results of preprocessing steps

borhood shape is a straight line with length N pixel, unlike in LBP, which is a square [11]. The straight-line shape of LLBP can extract robust features from the images with unclear veins, it is more suitable to capture the pattern in a vein image [12]. In line with this, we propose dorsal hand vein recognition system based on the local feature using Local Binary Pattern (LLBP) method. Therefore, recognition performance of dorsal hand vein image will be good.

In recognition stage, there are two types of methods that can be used. The first one is using threshold distance [15] and the other one is using classification methods. There is a weakness when we use threshold distance [16]. The accuracy result from dorsal hand vein recognition will be strongly depend on the threshold value. It can make the optimal accuracy result hard to find. So that, classification method is implemented for a number of studies in hand vein recognition cases such as fuzzy-neuro technique [17], k-NN [16], fuzzy k-NN [12] and back-propagation neural network [17]. In this experiment, we considered the fuzzy k-NN to be a suitable classifier since it does not need any learning algorithm, unlike in fuzzy-neuro technique and back-propagation neural network, so that it can decrease the processing time [18]. Moreover, due to the feature of dorsal hand vein image that similar to each other, we choose fuzzy k-NN method over k-NN method to avoid the false recognition of dorsal hand vein image.

The aim of this paper is to apply feature extraction techniques, LLBP, to obtain a good




Figure 5. Example of LLBP operator

definition of the vein pattern. And to **13** opt classification method, fuzzy k -NN, to obtain a good performance in the **13** accuracy with speedy matching. After analysing the related works in the section on **1** introduction, we will briefly introduce the proposed method for dors **2** hand vein recognition in the section on Methods. Experimental results are presented and **40** discussed in the section on Results and Analysis to ve **23** the validity of the proposed approach. Finally, concluding remarks and future works are given in the section on Conclusion.

2. Methods

22 The block diagram of the proposed method for dorsal hand vein recognition showed in Figure 1. The method consists of five main stages: image acquisition, ROI (Region of Interest) extraction, preprocessing, feature extraction by Local Line Binary Pattern (LLBP) and dorsal hand vein recognition by the Fuzzy k -NN classifier.

4 Image Acquisition

To the best of our knowledge, there is no currently publicly a **6** able dorsal hand vein database. Therefore, in this paper, we set up multispectral dorsal hand vein image databases with our vein image capture device. One of the purposes of our research is to create a capture setup that is efficient and has a low cost. A cheap infrared webcam (M-Tech Webcam) was chosen to be used for taking the pictures of the hand. The came **6** has been modified so it can capture NIR images. As the infrared light can penetrate biological tissue and the venous blood absorbs more infrared light than the surrounding tissue, the vein appears darker **9** in the surrounding tissue in an NIR image. A vein pattern reveals the vast network of blood vessels underneath the skin [3].



Figure 6. The extracted feature using LBP (a) and LLBP (b)

6 We capture a total of 300 dorsal hand vein images. This dataset consists of 6 left dorsal hand vein images of 50 individuals (six samples per individual). These 6 images were acquired from each user **28** variant rotation. The collected dorsal hand vein image sample is shown in Figure 3. The dark line in the captured image is the vein.

ROI Extraction

2 The features of vein patterns extracted from the same region in different dorsal hand vein images are compared for recognition step. The extracted **33** ion is known as the region of interest (ROI). The acquired image is first converted to a grayscale image and then its ROI extracted using default cropping function from Matlab. Therefore, in this work, the ROI of dorsal hand vein image has been manually located.

Preprocessing

2 After ROI extraction, the next step is preprocessing. To ensure that the proper vein features can be extracted from the dorsal hand vein image, it is essential to preprocess the images. First, resize the image using Bicubic Interpolation method which the dimension is 128 x 128 pixels. The resized dorsal hand vein patterns were then preprocessed using Histogram Equalization function which enhances the contrast of the images. This method is useful if the researcher uses FIR imagin **47** technique since this method redistributed the pixel intensity thus changing the sharpness and contrast of image [17]. Thirdly, we use Anisotropic Diffusion filter to make the image smoother so the edge can be detected more specific in the next step. The Morphological operations namely closing operation are applied to the filtered image to get a thinned image. Then, subtract the filtered image with the closing operation image to get the pattern of the vein. Finally, normalize the subtracted image. The following figure shows the results of the preprocessing steps.




Figure 7. The Testing Result of Different k Values




Figure 8. Testing results of two different extracted ROI image datasets

Feature Extraction

In this research, the texture feature of dorsal hand vein image is extracted so that vein can be seen clearly. We use the Local Line Binary Pattern (LLBP) method to extract the feature and compare the result LLBP with the result of the previous method, Local Binary Pattern (LBP) method.

The Local Binary Pattern (LBP) operator is a texture descriptor based on the gray level comparison of a neighborhood of pixels [9]. The original operator considers a 3x3 neighborhood of 8 pixels in around a center pixel i_c . The threshold $s(x)$, for these neighborhood pixels, is the value of the center pixel and the result considered as a binary number or its decimal equivalent LBP (x_c, y_c) [9]. LBP operator showed in Equation (1), and the threshold for the neighborhood pixels showed in Equation (2) [11].

$$LBP(x_c, y_c) = \sum_{n=0}^7 (i_n - i_c) 2^n \tag{1}$$

$$s(x) = \begin{cases} 1, & \text{if } x \geq 0 \\ 0, & \text{if } x < 0 \end{cases} \tag{2}$$

Motivated by LBP, Petpon and Srisuk [13] proposed an LLBP operator for face recognition. The operator consists of two components: horizontal component (LLBPh) and a vertical component (LLBPv). The magnitude of LLBP can be obtained by calculating the line binary codes for both components. The main difference between LLBP and original LBP are as follows: 1) the LLBP operator has a straight shape line, this will greatly assist LLBP operator in capturing the change in image intensity. 2) The pattern of the image at left and right side of the center pixel of the line are a mirror because of the distribution of binary weight at left, and the right side is equal. Thus, the number of patterns can be reduced [5]. The illustration of LLBP operator is shown in Figure 5, and its

mathematic definitions are given in Equations (3) - (5) [11].

$$LLBP_{hN,c}(x, y) = \sum_{n=1}^{c-1} s(h_n - h_c) \cdot 2^{c-n-1} \tag{3}$$

$$+ \sum_{n=c+1}^N s(h_n - h_c) \cdot 2^{n-c-1} \tag{4}$$

$$LLBP_{vN,c}(x, y) = \sum_{n=1}^{c-1} s(v_n - v_c) \cdot 2^{c-n-1} \tag{5}$$

$$+ \sum_{n=c+1}^N s(v_n - v_c) \cdot 2^{n-c-1}$$

$$LLBP_m = \sqrt{LLBP_h^2 + LLBP_v^2} \tag{5}$$

LLBPh, LLBPv, and LLBpm are LLBP on horizontal direction, vertical direction, and its magnitude, respectively. N is the length of the line in the pixel, h_n is the pixel along with the horizontal line, and v_n is the pixel along with the vertical line. $c = N/2$ is the position of the center pixel, h_c on the horizontal line and v_c on the vertical line, and $s(\bullet)$ function defines a thresholding function as in Equation (2).

Employing Equations (2) and (3), the horizontal component of LLBP (LLBPh) extracts a binary code of $N - 1$ bits for each pixel. The same numbers of bits are extracted by the vertical component of LLBP (LLBPv) using Equations (2) and (4). Each ROI vein image is extracted by this coding method into LLBP feature vectors which dimension is 128×128 . Figure 6 shows the results of feature extraction using LBP and LLBP, respectively.




Figure 9. The performance comparison of LBP and LLBP method

Recognition

We use a Fuzzy k-NN classifier to match the extracted dorsal hand vein image from testing data with the one from training data. The basic concept of this classifier is to assign membership as a function of the object's distance from its k-nearest neighbors and the memberships in the possible class l.

Consider $W = \{w_1, w_2, \dots, w_m\}$ a set of m labeled data, x is the input for classification, k is the number of closest neighbors of x , and E is the set of k nearest neighbors (NN). Let $\mu_i(x)$ is the membership of x in the class i , m be the number of elements that identify the classes l , and W be the set that contains some m elements. To calculate $\mu_i(x)$, we use Equation (6) [18].

$$\mu_i(x) = \frac{\sum_{j=1}^k \mu_{ij} \left(\frac{1}{\|x - m_j\|^{2/(m-1)}} \right)}{\sum_{j=1}^k \left(\frac{1}{\|x - m_j\|^{2/(m-1)}} \right)} \quad (6)$$

Since we use the Fuzzy k-NN method, each element of x testing data is classified in more than one class with membership value $\mu_i(x)$. The decision to which class the element of x testing data belongs is made according to which class the element of x testing data has the highest membership value $\mu_i(x)$.

3. Results and Analysis

The proposed method was implemented in Matlab R2011b and evaluated using our multispectral dorsal hand vein database. To demonstrate the robustness of the proposed approach, in our experiments, the total number of dorsal hand vein

TABLE 1
THE TESTING RESULT OF LLBP METHOD ON
RIGHT DORSAL HAND AND
LEFT DORSAL HAND VEIN DATABASE

| K-Fold | Accuracy (%) | |
|-------------|--------------|-----------|
| | Right-hand | Left-hand |
| 1 | 100 | 100 |
| 2 | 90 | 100 |
| 3 | 90 | 90 |
| 4 | 100 | 90 |
| 5 | 100 | 100 |
| 6 | 100 | 100 |
| Average (%) | 96.7 | 96.7 |

TABLE 2
COMPARISON OF FUZZY K-NN AND THE OTHER
CLASSIFICATION METHOD

| Method | Accuracy (%) | Time |
|--------------------------|--------------|-------|
| Neural Network | 97.25 | 187.5 |
| K-Nearest Neighbor | 78 | 37.5 |
| Fuzzy K-Nearest Neighbor | 98 | 37.8 |

images contains over 50 classes. There are 6 sample images of each left dorsal hand. In total, the database contain 5000 images. The spatial and depth resolution of the dorsal hand vein images were 1280×960 pixel and 256 gray levels, respectively.

To evaluate the proposed method for dorsal hand vein recognition, the experiments were conducted in five modes. The first experiment is conducted to show the comparison of fuzzy k-NN and k-NN method in recognition stage. Thus we use $k=1$ (for k-NN method) and $k=2, k=3, k=4, k=5$ (for fuzzy k-NN). The second experiment is conducted to show how parameter N of LLBP affects the recognition result of the proposed method. The third experiment is conducted to analyze the relationship between ROI image extraction and performance of the proposed method. The fourth experiment is conducted to evaluate the effectiveness of the proposed method for dorsal hand vein recognition by comparing its accuracy with LBP method. Then, the fifth experiment is conducted to apply the approach method on 60 right dorsal hand vein images obtained from 10 individuals (six samples per individual). These ten individuals are randomly chosen from our databases.

In all experiments, if the test sample and the found template are from the same class, this is a correct recognition. Therefore, the proposed algorithm can be measured by correct recognition rate (CRR), the ratio of the number of samples being correctly classified to the total number of test samples. Using K-fold cross-validation procedure with $K=6$, we split data into six folds. In every K-fold, data was divided into 250 databases and 50 testing data that each dorsal hand of a person will

have 5 sample images as database and an image sample as testing data, respectively.

In the first experiment, we used five different k values: $k=1$ (for k -NN), and $k=2, k=3, k=4, k=5$ (for fuzzy k -NN). Then, we compare the accuracy of each k , k is the number of closest neighbors that used when data is being classified. Figure 7 shows the experimental results.

As can be seen in Figure 7, the highest recognition result obtained from $k=2$ (fuzzy k -NN) with 96.3% of accuracy while the lowest is obtained from $k=1$ (k -NN) with 78% of accuracy. Considering the result of experiment 1, we use $k=2$ (fuzzy k -NN) for the next four experiments.

In this paper, we used the LLBP method to extract the features of the dorsal hand vein. However, there is an N -variable that represents the amount of neighbourhood pixel that used in LLBP. Therefore, in the second experiment, we tested LLBP method with six different N values ($N=7, 9, 11, 13, 15, \text{ and } 17$). And we find that all six different N values are equal in accuracy with the highest recognition result obtained from k -fold 1-3 with 98% of accuracy while the lowest is obtained from k -fold 4-5 with 94% of accuracy. This result proves that the number of neighbourhood pixel used for LLBP does not affect the recognition performance in this research. Therefore, we use the standard value of $N, N=13$ [13], as the number of neighborhood pixels for LLBP method for the next following experiments.

A further analysis of the proposed method is made by conducting the third experiment. In this experiment, we use two different extracted ROI image datasets: Testing 1 and Testing 2. Testing 1 is the extracted ROI image datasets which obtained randomly whereas Testing 2 obtained with fixing process. The experimental results of these two different extracted ROI image datasets is showed in Figure 8.

As can be seen in Figure 8, Testing 2 has higher accuracy compared to Testing 1. From 6-fold cross validation, the Testing 2 has accuracy up to 96.3% whereas the Testing 1 has accuracy up to 92.70%. These experimental results demonstrate that our current method depends on extracted ROI image. Thus, it is evident that the fixing process has a significant influence on the accuracy of verification. Since the ROI has been manually located, it cannot ensure that the ROI will always be in the same position in different dorsal hand vein images. Because of the unstable ROI extraction, there are some false recognized dorsal hand vein images. It is important to fix the ROI in the same position of different dorsal hand vein images to ensure the stability of the principal extracted vein features.

In this research, we also applied the LBP method on our dorsal hand vein image database to extract the vein feature and compare its accuracy with LLBP method. This experimental result will demonstrate the excellent performance of the proposed method. From the results shown in Figure 9, we can find that our proposed method, LLBP method, has higher accuracy compared to LBP method. From 6-fold cross validation, LLBP has accuracy up to 96.3% whereas LBP method has accuracy up to 81.0%.

The LLBP method, is a new approach of Local Binary Pattern (LBP). The LLBP operator has a straight-line shape; this will greatly assist LLBP operator in capturing the change in image intensity. Therefore, LLBP can extract robust features from the images with unclear veins it is more suitable to capture the pattern inside a dorsal hand vein image. Vein feature in extracted image using LLBP method is more distinct than vein feature in extracted image using LBP method as can be seen in Figure 6. The more distinct feature extracted, the higher the accuracy we get. Furthermore, we find that the accuracy of our proposed method, LLBP, is better than the accuracy of the previous method, LBP.

To further prove the effectiveness of the proposed method, we employed 60 right dorsal hand vein images obtained from 10 different individuals that we randomly choose from our database. Then we make a detailed comparison between right dorsal hand vein images and left dorsal hand vein images with same total images. Table 2 details the experimental result.

From the results shown in Table 1, we can find that our proposed method has a good performance of 96.7% recognition accuracy for both right dorsal hand vein and left dorsal hand vein database. This is because our method well characterizes line-based features of the dorsal hand vein. Additionally, this method keeps the original form of local shape and achieves good information of the vein texture. Thus, we conclude that LLBP method is suitable for dorsal hand vein feature extraction.

Further analysis of classification method is made by comparing the performance of fuzzy k -NN and the other classification method, k -NN [16] and Neural Network algorithm [17] using 300 dorsal hand vein images. From the result shown in Table 2, we can find that fuzzy k -NN tends to be faster on matching time and provides the highest accuracy of recognition

4. Conclusion

We present a reliable and robust biometric-based

Recognition approach by using our multispectral dorsal hand vein images. To capture the line-based features of the dorsal hand vein and match different dorsal hand vein images, we proposed the Local Line Binary Pattern (LLBP) method. Compared to the existing method such as Local Binary Pattern (LBP), LLBP method is more reliable than LBP method for feature extraction on dorsal hand vein recognition with a recognition accuracy up to 98% on our left dorsal hand vein database. Moreover, using fuzzy k-NN method, the system can achieve higher recognition accuracy than the other classification method. Therefore, we conclude that the proposed method, LLBP for feature extraction and fuzzy k-NN method for recognition stage, is promising for dorsal hand vein recognition.

Through experimentation, it is also found that different techniques of ROI extraction give different results which have an impact on the later stages. The result proves that a well-defined extracted vein pattern gives better performance and leads to a more secure biometric authentication system. In future, an experiment conducted to obtain the better extracted ROI image is needed

References

- [1] D. Zhang, Z. Guo, & Y. Gong, "Multispectral biometrics systems," *Multispectral biometrics*. Springer, Cham, pp. 23-35, 2016.
- [2] K.R. Park, "Finger vein recognition by combining global and local features based on SVM," *Computing and Informatics*, vol. 30(2), pp. 295-309, 2012.
- [3] C.B. Hsu, J.C. Lee, S.J. Chuan, & P.Y. Kuei, "Gaussian directional pattern for dorsal hand vein recognition," *The Imaging Science Journal*, vol. 63(1), pp. 54-62, 2015.
- [4] Z. Honarpisheh, & K. Faez, "Biometric Identification by Clustering the Dorsal Hand Vein Patterns using the Firefly Algorithm," *International Journal of Electrical and Computer Engineering (IJECE)*, vol. 3(1), pp. 30-41, 2013.
- [5] C. Nandini, C. Ashwini, M. Aparna, N. Ramani, P. Kini, & K. Sheeba, "Biometric authentication by dorsal hand vein pattern," *International Journal of Engineering and Technology*, vol. 2(15), pp. 837-840, 2012.
- [6] X. Xinyan, F. Bin, W. Kejun, L. Fangming, & L. Zuowen, "Vein Texture Extraction Using the Multiscale SecondOrder Differential Model," *TELKOMNIKA Indonesian Journal of Electrical Engineering*, vol. 11(12), pp. 7470-7475, 2013.
- [7] G. Sikka, & E.V. Wasson, "Palm Vein Recognition with Fuzzy-Neuro Technique," *International Journal for Advance Research in Engineering and Technology*, vol. 2 (12), pp. 15-22, 2014.
- [8] L. Mirmohamadsadeghi, & A. Drygajlo, "Palm vein recognition with local texture patterns," *IET Biometrics*, vol. 3(4), pp. 198-206, 2014.
- [9] T. Ojala, M. Pietikainen, & T. Maenpaa, "Multiresolution gray-scale and rotation invariant texture classification with local binary patterns," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 24(7), pp. 971-987, 2002.
- [10] H. Khusnuliawati, C. Fatichah, & R. Soelaiman, "Multi-feature Fusion Using SIFT and LBP for Finger Vein Recognition," *TELKOMNIKA Indonesian Journal of Electrical Engineering*, vol. 15(1), pp. 478-485, 2017.
- [11] B.A. Rosdi, C.W. Shing, & S.A. Suandi, "Finger vein recognition using local line binary pattern," *Sensors*, vol. 11(12), pp. 11357-11371, 2011.
- [12] J.Y. Sari, C. Fatichah, & N. Suciati, "Local line binary pattern for feature extraction on palm vein recognition," *Jurnal Ilmu Komputer dan Informasi*, vol. 8(2), pp. 116-123, 2015.
- [13] A. Petpon, & S. Srisuk, "Face recognition with local line binary pattern," In *Image and Graphics, 2009. ICG'09. 5th International Conference*, Xi'an, pp. 533-539, 2009.
- [14] Y. Lu, S. Yoon, S.J. Xie, J. Yang, Z. Wang, & D.S. Park, "Finger Vein Recognition Using Generalized Local Line Binary Pattern," *KSH Transactions on Internet & Information Systems*, vol. 8(5), 2014.
- [15] L. Chen, H. Zheng, L. Li, P. Xie, & S. Liu, "Near-infrared dorsal hand vein image segmentation by local thresholding using grayscale morphology," In *1st International Conference on Bioinformatics and Biomedical Engineering (iCBBE2007)*, Wuhan, pp. 868-871, 2007.
- [16] A. Aghakabi, & S. Zokaee, "Fusing dorsal hand vein and ECG for personal identification," In *Electrical and Control Engineering (ICECE)*, International Conference, Yichang, pp. 5933-5936, 2011.
- [17] M.E.C. Villariña, & N.B. Linsangan, "Palm Vein Recognition System using Directional Coding and Back-propagation Neural Network," *IAENG*, in *Proceedings of the World Congress on Engineering and Computer Science*, San Francisco, vol. 2, 2015.
- [18] J.M. Keller, M.R. Gray, & J.A. Givens, "A fuzzy k-nearest neighbor algorithm," *IEEE*

102 *Jurnal Ilmu Komputer dan Informasi (Journal of a Science and Information)*, volume 11, issue 2, June 2018

Transactions on Systems, Man and
Cybernetics, vol. 15, 580-585, 1985.

ORIGINALITY REPORT

%**28**

SIMILARITY INDEX

%**12**

INTERNET SOURCES

%**25**

PUBLICATIONS

%**14**

STUDENT PAPERS

PRIMARY SOURCES

- | | | |
|----------|--|------------|
| 1 | Jen-Chun Lee, Tsung-Ming Lo, Chien-Ping Chang. "Dorsal hand vein recognition based on directional filter bank", Signal, Image and Video Processing, 2014 Publication | % 2 |
| 2 | www.mva-org.jp Internet Source | % 2 |
| 3 | nlpr-web.ia.ac.cn Internet Source | % 2 |
| 4 | Multispectral Biometrics, 2016. Publication | % 2 |
| 5 | cirworld.org Internet Source | % 1 |
| 6 | Zhaohui Meng, Xiaodong Gu. "Palm-Dorsal Vein Recognition Method Based on Histogram of Local Gabor Phase XOR Pattern with Second Identification", Journal of Signal Processing Systems, 2013 Publication | % 1 |
-

7

Inshirah Rossan, Maleika Heenaye-Mamode Khan. "Impact of Changing Parameters when Preprocessing Dorsal Hand Vein Pattern", *Procedia Computer Science*, 2014

Publication

% 1

8

Lu, Yu, Shan Juan Xie, Sook Yoon, and Dong Sun Park. "Finger vein identification using polydirectional local line binary pattern", 2013 International Conference on ICT Convergence (ICTC), 2013.

Publication

% 1

9

Jen-Chun Lee. "A novel biometric system based on palm vein image", *Pattern Recognition Letters*, 2012

Publication

% 1

10

ijesrt.com

Internet Source

% 1

11

Raghavendra, R., Jayachander Surbiryala, and Christoph Busch. "Hand dorsal vein recognition: Sensor, algorithms and evaluation", 2015 IEEE International Conference on Imaging Systems and Techniques (IST), 2015.

Publication

% 1

12

Mirmohamadsadeghi, Leila, and Andrzej Drygajlo. "Palm vein recognition with local texture patterns", *IET Biometrics*, 2014.

Publication

% 1

| | | |
|----|--|------|
| 13 | Lecture Notes in Computer Science, 2013. Publication | % 1 |
| 14 | Kuang-Shyr Wu, Jen-Chun Lee, Tsung-Ming Lo, Ko-Chin Chang, Chien-Ping Chang. "A secure palm vein recognition system", Journal of Systems and Software, 2013 Publication | % 1 |
| 15 | Submitted to Netaji Subhas Institute of Technology Student Paper | % 1 |
| 16 | Submitted to University of Technology Student Paper | % 1 |
| 17 | Submitted to Kennesaw State University Student Paper | % 1 |
| 18 | Yen-Po Lee. "Palm vein recognition based on a modified $\text{2D}^2\text{LDA}$ ", Signal, Image and Video Processing, 2013 Publication | % 1 |
| 19 | Submitted to The Hong Kong Polytechnic University Student Paper | % 1 |
| 20 | Submitted to Charotar University of Science And Technology Student Paper | <% 1 |
| 21 | www.neliti.com Internet Source | <% 1 |

-
- 22 Randa Boukhris Trabelsi, Alima Damak Masmoudi, Dorra Sellami Masmoudi. "Hand vein recognition system with circular difference and statistical directional patterns based on an artificial neural network", *Multimedia Tools and Applications*, 2014
Publication <% 1
-
- 23 link.springer.com
Internet Source <% 1
-
- 24 Fereshte Yazdani, Mehran Emadi Andani. "Verification based on palm vein by estimating wavelet coefficient with autoregressive model", 2017 2nd Conference on Swarm Intelligence and Evolutionary Computation (CSIEC), 2017
Publication <% 1
-
- 25 jisikworld.com
Internet Source <% 1
-
- 26 garuda.ristekdikti.go.id
Internet Source <% 1
-
- 27 Submitted to Universiti Kebangsaan Malaysia
Student Paper <% 1
-
- 28 Shangqing Wei, Xiaodong Gu. "A method for hand vein recognition based on Curvelet Transform phase feature", *Proceedings 2011 International Conference on Transportation*, <% 1

Mechanical, and Electrical Engineering (TMEE), 2011

Publication

29

Lee, Jen-Chun. "A novel biometric system based on palm vein image", *Pattern Recognition Letters*, 2012.

Publication

30

Susheel Kumar Yadav, Dharendra Pratap Singh, Jaytrilok Choudhary. "A Survey: Comparative Analysis of Different Variants of Local Binary Pattern", 2018 Second International Conference on Inventive Communication and Computational Technologies (ICICCT), 2018

Publication

31

Meng, Xianjing, Gongping Yang, Yilong Yin, and Rongyang Xiao. "Finger Vein Recognition Based on Local Directional Code", *Sensors*, 2012.

Publication

32

text-id.123dok.com

Internet Source

33

Zhaohui Meng, Xiaodong Gu. "Hand vein identification using local Gabor ordinal measure", *Journal of Electronic Imaging*, 2014

Publication

34

www.ferasdayoub.com

Internet Source

<% 1

<% 1

<% 1

<% 1

<% 1

<% 1

35

www.sersc.org

Internet Source

<% 1

36

Submitted to Universitas Brawijaya

Student Paper

<% 1

37

Wei-Yu Han, Jen-Chun Lee. "Palm vein recognition using adaptive Gabor filter", *Expert Systems with Applications*, 2012

Publication

<% 1

38

ir.library.osaka-u.ac.jp

Internet Source

<% 1

39

Submitted to Higher Education Commission Pakistan

Student Paper

<% 1

40

Xi, Xiaoming, Gongping Yang, Yilong Yin, and Xianjing Meng. "Finger Vein Recognition with Personalized Feature Selection", *Sensors*, 2013.

Publication

<% 1

41

documents.mx

Internet Source

<% 1

42

Yiding Wang, Di Zhang, Qi Qi. "Liveness detection for dorsal hand vein recognition", *Personal and Ubiquitous Computing*, 2016

Publication

<% 1

43

Huabin Wang, Mengli Du, Jian Zhou, Liang Tao.

"Weber Local Descriptors With Variable Curvature Gabor Filter for Finger Vein Recognition", IEEE Access, 2019

Publication

<% 1

44

Submitted to Multimedia University

Student Paper

<% 1

45

www.cse.uconn.edu

Internet Source

<% 1

46

Submitted to King Abdulaziz University

Student Paper

<% 1

47

www.ijitee.org

Internet Source

<% 1

48

R.R.O. Al-Nima, M.A.M. Abdullah, M.T.S. Al-Kaltakchi, S.S. Dlay, W.L. Woo, J.A. Chambers. "Finger texture biometric verification exploiting Multi-scale Sobel Angles Local Binary Pattern features and score-based fusion", Digital Signal Processing, 2017

Publication

<% 1

49

Jun Wang, Guoqing Wang. "Quality-Specific Hand Vein Recognition System", IEEE Transactions on Information Forensics and Security, 2017

Publication

<% 1

50

Renke Zhang, Di Huang, Yunhong Wang. "Textured detailed graph model for dorsal hand

<% 1

vein recognition: A holistic approach", 2016
International Conference on Biometrics (ICB),
2016

Publication

51

Shark, Lik-Kwan, Ke Zhang, and Yiding Wang. "Personal identification based on multiple keypoint sets of dorsal hand vein images", IET Biometrics, 2014.

Publication

<% 1

52

Zhixing Huang, Wenxiong Kang, Qiuxia Wu, Junhong Zhao, Wei Jia. "Chapter 27 A Finger Vein Identification System Based on Image Quality Assessment", Springer Nature, 2016

Publication

<% 1

53

Amira Oueslati, Nadia Feddaoui, Kamel Hamrouni. "Identity Verification Through Dorsal Hand Vein Texture Based on NSCT Coefficients", 2017 IEEE/ACS 14th International Conference on Computer Systems and Applications (AICCSA), 2017

Publication

<% 1

EXCLUDE QUOTES ON

EXCLUDE
BIBLIOGRAPHY ON

EXCLUDE MATCHES

< 5
WORDS